

CLEANAIR FILTRATION SYSTEM STANDALONE

VOLTAGE: 230 V1 PHASE **FAN AMPS:** 2.9 A CAPACITOR: 14 UF **FAN CFM: 2000 BOX MATERIAL:** ALUMINUM **BOX COLOR:** PROTO GREY **DB RATING:** 58 **RETURN AIRFLOW:** ALL 4 SIDES **SUPPLY AIRFLOW:** ANY SIDE(S) (up to all 4) **STAGE 1:** 1" PRE-FILTER, MERV 2 **STAGE 2:** 4" HIGH-EFFICIENCY FILTER, MERV 1-15 (99% of PARTICULATE) **STAGE 3:** DOUBLE TRAY, 20 LB COCONUT CARBON **STAGE 4:** DOUBLE TRAY, 30 LB COCONUT CARBON **STAGE 5: OPTIONAL UV AIR PURIFICATION WEIGHT:** 215 | B

NOTABLES:

WILL SCRUB AREAS OF UP TO 15,000 CUBIC FEET.

COMPOSITE BLOWER FAN WITH INTEGRATED MOTOR FOR HARSH ENVIRONMENTS.

4" HIGH-EFFICIENCY FILTER IS DESIGNED TO REMOVE UP TO 99% OF AIRBORNE PARTICULATE.

CUSTOM COCONUT CARBON CHARCOAL IS SPECIFICALLY DESIGNED TO REMOVE HARSH ORGANIC ODORS..

OPTIONAL UV AIR PURIFIER INTEGRATION (UVC GERMICIDAL BULB RUNNING AT 254 NM WAVELENGTH, KILLING SPORES, BACTERIA & MILDEW).

EXCEL AIR SYSTEMS 120-20170 STEWART CRES. MAPLE RIDGE, BC V2X 0T4 CANADA TEL/FAX: 1-877-728-0757 SALES@EXCELAIRSYSTEMS.COM

