

| FRONT | | EVOLUTION SERIES CONDENSER |
|-------|--|---|
| | <image/> <image/> <image/> <image/> <image/> | 4-TON (48,000 BTU) VOLTAGE: 230 V1 PHASE FAN AMPERAGE: 4.8 A (POWER SUPPLIED FROM AIR HANDLER) CAPACITOR: 16 UF FAN DIAMETER: 25" MATERIAL: CAST WINGTIP RPM: 990 FAN CFM: 4500 DB RATING: 55 / 62 / 69 COIL: SLAB MICROCHANNEL COIL FACE: 30" X 30" CAPACITY: 48,000 BTU REFRICERANT: R-410A LIQUID LINE: 3/8" DISCHARGE LINE: 5/8" CONTROL CONNECTION: 9-PIN TURN & LOCK MODULATION: LOW AMBIENT CONTROLLER (-35 °F) WEIGHT: 126 LB |
| SIDE | THE | NOTABLES: POWER IS SUPPLIED FROM INDOOR AIR HANDLER. MINIMUM CLEARANCE FROM WALL IS 9". CAN BE ELEVATED AND BRACKETED TO WALL. UNIT COMES IN BOTH PRE-CHARGED QUICK-CONNECT OR PRO SERIES HARD PIPED. LOW AMBIENT SENSOR IS INTEGRATED WITHIN THE COIL. .STL FILES ARE AVAILABLE UPON REQUEST. EXCEL AIR SYSTEMS MAPLE RIDGE, BC V2X 014 |