

FRONT		EVOLUTION SERIES CONDENSER
	<image/> <image/> <image/> <image/> <image/> <image/>	5-TON (60,000 BTU) VOLTAGE: 230 V1 PHASE FAN AMPERAGE: 4.8 A (POWER SUPPLIED FROM AIR HANDLER) CAPACITOR: 16 UF FAN DIAMETER: 25" MATERIAL: CAST WINGTIP RPM: 990 FAN CFM: 4500 DB RATING: 55 / 62 / 69 COIL: SLAB MICROCHANNEL COIL FACE: 30" X 30" CAPACITY: 60,000 BTU REFRICERANT: R-410A LIQUID LINE: 3/8" DISCHARGE LINE: 5/8" CONTROL CONNECTION: 9-PIN TURN & LOCK MODULATION: LOW AMBIENT CONTROLLER (-35 °F) WEIGHT: 126 LB
SIDE	THE THE PARTY OF T	NOTABLES: POWER IS SUPPLIED FROM INDOOR AIR HANDLER. MINIMUM CLEARANCE FROM WALL IS 9". CAN BE ELEVATED AND BRACKETED TO WALL. UNIT COMES IN BOTH PRE-CHARGED QUICK-CONNECT OR PRO SERIES HARD PIPED. LOW AMBIENT SENSOR IS INTEGRATED WITHIN THE COIL. .STL FILES ARE AVAILABLE UPON REQUEST. EXCEL AIR SYSTEMS PROSENT SEWART CRESS. MAPLE RIDGE, BC V2X 014